

TREILLIS SOUDES EN PANNEAUX

CARACTÉRISTIQUES DES TREILLIS SOUDES

	Type	Section cm ² /m	Maille mm	Fils mm	mm.mm	Nbr de fils	Largeur	Masse nominale Kg/m ²	Surface panneau m ²	Poids panneau kg	Nbr par fardeau
			Ee	Dd	ad.ag	n					
EN STOCK	PAF R	0.80	200	4.5	150/150	12	3.60	1.042	8.64	9.00	100
		0.53	300	4.5	100/100	12	2.40				
	PAF C	0.80	200	4.5	100/100	12	3.60	1.250	8.64	10.80	100
		0.80	200	4.5	100/100	18	2.40				
SUR COMMANDE	RAF R	0.80	200	4.5	100/100	12	50	1.043	120.00	125.10	1
		0.53	300	4.5	100/100	167	2.40				
	RAF C	0.80	200	4.5	100/100	12	40	1.250	96.00	120.00	1
0.80		200	4.5	100/100	200	2.40					
	PAF F	0.80	200	4.5	135/25	12	3.20	1.250	7.68	9.60	100
		0.99	160	4.5	100/100	16	2.40				
EN STOCK	PAF 10	1.19	200	5.5	100/100	12	4.20	1.87	10.08	18.85	50
		1.19	200	5.5	100/100	24	2.40				
	ST 20	1.89	150	6.0	150/150	16	6.00	2.487	14.40	35.81	50
		1.28	300	7.0	75/75	20	2.40				
	ST 25	2.57	150	7.0	150/150	16	6.00	3.020	14.40	43.49	40
		1.28	300	7.0	75/75	20	2.40				
	ST 30	2.83	100	6.0	150/150	24	6.00	3.226	14.40	46.46	35
1.28		300	7.0	50/50	20	2.40					
ST 35	3.85	100	7.0	150/150	24	6.00	4.026	14.40	57.98	30	
	1.28	300	7.0	50/50	20	2.40					
ST 50	5.03	100	8.0	150/150	24	6.00	5.267	14.40	75.84	20	
	1.68	300	8.0	50/50	20	2.40					
ST 60	6.36	100	9.0	125/125	24	6.00	6.986	14.40	100.60	16	
	2.54	250	9.0	50/50	24	2.40					
TREILLIS FONDACTIONS	ST 15C	1.42	200	6.0	100/100	12	4.00	2.220	9.60	21.31	50
		1.42	200	6.0	100/100	20	2.40				
	ST 25C	2.57	150	7.0	75/75	16	6.00	4.026	14.40	57.98	30
		2.57	150	7.0	75/75	40	2.40				
SUR COMMANDE	ST 25 CS	2.57	150	7.0	75/75	16	3.00	4.026	7.20	28.99	40
		2.57	150	7.0	75/75	20	2.40				
	ST 40 C	3.85	100	7.0	50/50	24	6.00	6.040	14.40	86.98	20
		3.85	100	7.0	50/50	60	2.40				
	ST 50 C	5.03	100	8.0	50/50	24	6.00	7.900	14.40	113.76	15
		5.03	100	8.0	50/50	60	2.40				
	ST 65 C	6.36	100	9.0	50/50	24	6.00	9.980	14.40	143.71	10
		6.36	100	9.0	50/50	60	2.40				

